## LIST OF FIGURES

Figure 1.1	Research Methodology	3
Figure 1.2	Empirical Research Design	4
Figure 1.3	Data Collection and Analysis	5
Figure 2.1	Typical Silicon Solar Cell	12
Figure 2.2	Schematic representation of currents in a p-n junction under illumination	12
Figure 2.3	Equivalence circuit of PV Cell	13
Figure 2.4	Typical configuration of commercial PV Module	18
Figure 2.5	Typical Bypass diode configuration PV Module	19
Figure 2.6	Hot Spot Effect	19
Figure 2.7	Bypass Diode Effect	20
Figure 2.8	Module I-V Characteristics with Different Cells Totally Shadowed	22
Figure 2.9	Module I-V Characteristics with the Test Cell Shadowed at Different Levels	23
Figure 3.1	Fire Tetrahedron (Courtesy: Mine Emergency Response Program Mine Rescue Manual [21])	27
Figure 4.1	Solar Paths of Chennai	34
Figure 4.2	Normal I-V Characterisation (with BPD)	35
Figure 4.3	I-V Characteristics shift for one cell 90% shaded (without BPD)	35
Figure 4.4	I-V Characteristics shift for one cell 90% shaded (with 2 BPD/Module)	36
Figure 4.5	P-V Characteristics for unshaded and one cell 60% partially shaded module	37
Figure 4.6	P-V Characteristics for unshaded and one cell 90% partially shaded module	37
Figure 4.7	I-V Characteristics shift for two cells 90% shaded (without BPD)	38
Figure 4.8	I-V Characteristics shift for two cell 90% shaded (with 2 BPD/Module)	38
Figure 4.9	P-V Characteristics for unshaded and two cells 60% partially shaded module	39
Figure 4.10	P-V Characteristics for unshaded and two cells 90% partially shaded module	39
Figure 4.11	I-V Characteristics shift for five cells 90% shaded (without BPD)	40
Figure 4.12	I-V Characteristics shift for five cell 90% shaded (with 2 BPD/Module)	40
Figure 4.13	P-V Characteristics for unshaded and five cells 60% partially shaded module	41
Figure 4.14	P-V Characteristics for unshaded and five cells 90% partially shaded module	41
Figure 5.1	Schematic diagram of experimental set up	48

Figure 6.1	Experimental Setup	52
Figure 6.2	IV (Current-Voltage) curve for PV performance modules	54
Figure 7.1	Current–Voltage Performance of the 100 Wp - Poly Crystalline PV module	64
Figure 7.2	Power–Voltage Performance of the 100 Wp – Poly Crystalline PV module	65
Figure 7.3	Cell Partial Shade Temperature Rise Poly crystalline 100 Wp Module with bypass diode	66
Figure 7.4	Cell Partial Shade Temperature Rise Poly crystalline 100 Wp Module without bypass diode	67
Figure 7.5	Current–Voltage Performance of the 230 Wp – Poly Crystalline PV module	70
Figure 7.6	Power–Voltage Performance of the 230 Wp – Poly Crystalline PV module	71
Figure 7.7	Cell Partial Shade Temperature Rise - With Bypass Diode Poly crystalline 230 Wp 24V Module	72
Figure 7.8	Current–Voltage Performance of the 250 Wp – Mono Crystalline PV module	74
Figure 7.9	Power–Voltage Performance of the 250 Wp– Mono Crystalline PV module	75
Figure 7.10	Cell Partial Shade Temperature Rise - Bypass Diode Removed Mono crystalline 250 Wp 24V Module	76
Figure A.1	Normal I-V m-Si Characterisation (with BPD)	85
Figure A.2	m-Si I-V Characteristics shift for one cell 90% shaded (with 3 BPD/ Module)	85
Figure A.3	m-Si I-V Characteristics shift for one cell 90% shaded (without BPD)	86
Figure A.4	m-Si P-V Characteristics for unshaded and one cell 60% partially shaded module	86
Figure A.5	m-Si P-V Characteristics for unshaded and one cell 90% partially shaded module	87
Figure A.6	m-Si I-V Characteristics shift for two cell 90% shaded (with 3 BPD/ Module)	87
Figure A.7	m-Si I-V Characteristics shift for two cells 90% shaded (without BPD)	88
Figure A.8	m-Si P-V Characteristics for unshaded and two cells 60% partially shaded module	88
Figure A.9	m-Si P-V Characteristics for unshaded and two cells 90% partially shaded module	89
Figure A.10	m-Si I-V Characteristics shift for five cell 90% shaded (with 3 BPD/ Module)	80
Figure A.11	m-Si I-V Characteristics shift for five cells 90% shaded (without BPD)	90
Figure A.12	m-Si P-V Characteristics for unshaded and five cells 60% partially shaded module	90
Figure A.13	m-Si P-V Characteristics for unshaded and five cells 90% partially shaded module	91